



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B060-032

KVM Switch - 32-Port (4-User) 1U Rackmount Cat5 Matrix KVM Switch

Highlights

- Four consoles independently and simultaneously control up to 32 directly connected computers, or over 2,000 when additional KVM's are connected
- Multi-Platform support: PC, Sun, or Mac
- Rackmountable in a 1U design, with 32 available ports...Rackmount Hardware Included
- Inexpensive Cat5 cabling makes cable management a breeze; 500ft distance from Console to switch, or 500ft from Switch to Servers
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases



Description

Tripp Lite's 32-port NetDirector® 1U Rackmount Matrix KVM Switch is the optimal solution for controlling multiple computers (combination of PS/2, USB, or Sun) by four independent, simultaneous users. A single unit occupies a mere 1U of rack space, yet can control up to 32 computers. A maximum of 2,048 computers can be connected through a combination of daisy-chaining and cascading. RJ45 connections allow signals to travel up to 150 meters away(500ft), using ordinary Cat5 cable, while maintaining video resolution. Use either PS/2 or USB console equipment to connect to PS/2, USB, or SUN Servers.

For Government purchasers, B060-032 is Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

System Requirements

- Console: The Tripp Lite [B062-002-PS2](#) or [B062-002-USB](#) Console Interface Module must be used to connect a console (Keyboard, Monitor and Mouse) to the KVM switch
- Computers: The Tripp Lite [B054-001-SUN](#), [B054-001-PS2](#) or [B054-001-USB](#) Server Interface Module must be used to connect a computer/server to the KVM switch

Package Includes

- 1 - B060-032 KVM Switch
- 1 - Power Cord
- 1 - Daisy Chain Cable
- 1 - CD with Owner's Manual
- 1 set - Rackmount Hardware

Features

- Three Level password security: Super Administrator, Administrator, and Users
- Superior video quality - up to 1024 x 768 @ 60Hz at 500ft.
- Auto Signal Compensation (ASC) assures optimum video resolution for distances up to 500ft between the switch and the consoles or computers - no dip switch setting required
- PS/2 keyboard and mouse emulation - computers boot even when the console focus is elsewhere. Keep Alive feature ensures that the keyboard and mouse work properly even if the switch temporarily loses power

- Daisy chain up to 7 additional B060-032 KVM Switches
- Cascade up to 32 B060-032 KVM switches from each station on the chain
- Up to 2,048 computers on a daisy chained/cascaded installation
- No software required; convenient computer selection via intuitive hotkey combinations or On Screen Display (OSD) menus
- OSD port list automatically expands when stations are added - port names are automatically reconfigured when the station sequence is changed
- OSD screen automatically adjusts to resolution changes
- Hot pluggable; add or remove components without having to power off the switch
- USB & PS/2 Consoles can control any combination of USB, PS/2, or SUN computers
- LCD, VGA, SVGA, XGA, and MultiSync support; DDC2B
- Rackmount Hardware Included
- Lifetime firmware upgrading via flash ROM
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
# Of Users	4
Console	No
Port Control	Hotkeys, OSD
Max CPU	2048
PC/Server	VGA, USB or PS/2
Cat5 KVM Switch	Yes
IP Remote Access	YES WITH B051-000
UPC Codes	
Unit Carton UPC#	037332123008
PHYSICAL	
Color	Black
Style	1U Rackmount
LCD Monitor (in.)	Not Applicable
ENVIRONMENTAL	
BTUs	38.9 to 41.7
CONNECTIONS	
Ports	32

Related Items

Required Products

Related Model	Description	Qty.
B054-001-PS2	KVM Switch Accessories - PS/2 Server Interface Module for NetDirector Matrix KVM Switches	1
B054-001-SUN	KVM Switch Accessories - SUN Server Interface Module for NetDirector Matrix KVM Switches	1
B054-001-USB	KVM Switch Accessories - USB Server Interface Module for NetDirector Matrix KVM Switches	1

B062-002-PS2	KVM Switch Accessories - PS/2 Console Interface Module for NetDirector Matrix KVM Switches	1
--------------	--	---

Optional Products

Related Model	Description	Qty.
B021-000-17	Rackmount Console - 1U Rackmount Console with 17" LCD	1
B051-000	KVM Switch Accessories - IP Remote Access Unit	1
N001-003-GY	3-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-005-GY	5-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-007-GY	7-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-010-GY	10-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-014-GY	14-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-025-GY	25-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-050-GY	50-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-075-GY	75-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-100-GY	100-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-125-GY	125-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-200-GY	200-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
P770-013	13-ft. KVM Switch Daisychain Cable for B060 KVMs	1
P770-06M	20-ft. (6M) KVM Switch Daisychain Cable for B060 KVMs	1
P770-10M	33-ft. (10M) KVM Switch Daisychain Cable for B060 KVMs	1
WEXT3-KVM-RMNC	3-Year Extended Warranty - For B060-032 KVM Switch	1
WEXT5-KVM-RMNC	5-Year Extended Warranty - For B060-032 KVM switch	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2910.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.