ADAM-4060 ADAM-4068 ADAM-4069

4-ch Relay Output Module

8-ch Relay Output Module with Modbus®

8-ch Power Relay Output Module with Modbus







2 x plug-in terminal



C FCC

ADAM-4068



ADAM-4069



Specifications

General

Connectors

blocks (#14 ~ 22 AWG)

Power Consumption

0.8 W @ 24 V_{DC}

Watchdog Timer

Support Protocol

SUPPORT Protocol

SUPPORT Protocol

Relay Output

Resistance

Breakdown Voltage
 Channels
 2 x form A
 2 x form C
 Contact Rating (Resistive)
 AC: 0.6 A @ 125 V
 DC: 2 A @ 30 V
 0.6 A @ 110 V
 Initial Insulation
 I G Ω min. at 500 V_{DC}

Relay off Time (typical) 2 ms
Relay on Time (typical) 3 ms

Specifications

General

Connectors

 2 x plug-in terminal blocks (#14 ~ 28 AWG)

 Power Consumption

 0.6 W @ 24 V_{DC}

 System (1.6 second) & Communication
 Support Protocol

 ASCII command and Modbus/RTU

Relay Output

Resistance

■ Breakdown Voltage 500 V_{AC} (50/60 Hz)
■ Channels 4 x form A 4 x form C
■ Contact Rating (Resistive) AC: 0.5 A @ 120 V 0.25 A @ 240 V DC: 1 A @ 30 V 0.3 A @ 110 V
■ Initial Insulation 1 G Ω min. at 500 V_{DC}

Relay off Time (typical) 4 ms
 Relay on Time (typical) 3 ms

Specifications

General

Connectors 2 x plug-in terminal blocks (#14 ~ 28 AWG)
 Power Consumption 2.2 W @ 24 V_{DC}
 Watchdog Timer System (1.6 second) & Communication
 Support Protocol ASCII command and Modbus/RTU

Relay Output

■ Breakdown Voltage 1000 V_{AC} (50/60 Hz)
■ Channels 4 x form A 4 x form C
■ Contact Rating AC: 5 A @ 250 V DC: 5 A @ 30 V
■ Initial Insulation Resistance
■ Relay off Time (typical) 5.6 ms

Relay off Time (typical) 5.6 ms
 Relay on Time (typical) 5 ms

Common Specifications

■ **Power Input** Unregulated 10 ~ 30 V_{DC}

Environment

Humidity 5 ~ 95% RH
 Operating Temperature -10 ~ 70° C (14 ~ 158° F)
 Storage Temperature -25 ~ 85° C (-13 ~ 185° F)

Ordering Information

ADAM-4060 4-ch Relay Output Module
 ADAM-4068 8-ch Relay Output Module with Modbus

ADAM-4069 8-ch Power Relay Output Module with Modbus