

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO 60 °C ⁽¹⁾	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽¹⁾	
	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽¹⁾			
	OPERATING HUMIDITY RANGE	40 % TO 80 %.			
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	○	○	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK ⁽¹⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.			APPROVED	HS.OKAWA	06.10.17
			CHECKED	HS.OZAWA	06.10.17
			DESIGNED	KY.NAKAMURA	06.10.17
			DRAWN	AK.SUZUKAWA	06.10.16
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-021374-00
HRS	SPECIFICATION SHEET		PART NO.	A3-GPIN (A)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL621-0178-2-00	1/1