

126-00069

HellermannTyton

Article Number: 126-00069

Description: Wing Push Mount Cable Tie, 6.0" Long, 50lb Tensile, PA66, Natural, 500/bag

HellermannTyton

Base Data	Local Order Number	126-00069
	Type	T50SSFM
	Color	Natural (NA)
	Features and Benefits	<ul style="list-style-type: none"> • Wing design helps stabilize the tie in high-vibration applications. • Includes a ladder-type strap as opposed to a conventional serrated strap; giving the benefit of being extra flexible. • Wing design provides low insertion and high extraction force.
	Quantity Per	bag
	Product Description	Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.
	Short Description	Wing Push Mount Cable Tie, 6.0" Long, 50lb Tensile, PA66, Natural, 500/bag
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225N
Length L (Imperial)		6.3"
Length L (Metric)		160.0mm
Fixation Method		Arrowhead
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.18"
Width W (Metric)		4.6mm
Width W2 (Metric)		14.7mm
Height H (Imperial)		0.2"
Height H (Metric)		5.6mm

126-00069

HellermannTyton

Product Dimensions	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.7mm
	Mounting Hole Diameter D (Metric)	6.0 - 6.6 mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	bag