LED Heat Sink R150-170

This LED Heatsink is part of the Nuventix scalable LED portfolio.

Future proof - Designed with the rapidly evolving light engine industry in mind, thermal performance can be easily increased or decreased without a luminaire redesign by adding or removing a SynJet Cooler

Flexibility - Configure to order luminaire production process, use heatsinks for low lumen applications and the SynJet Cooler with heatsink for higher lumen versions

Freedom - Compatible with most major light engines so thermal solutions and mechanical interfaces do not have to be redesigned when changing light engines

Fast - In stock and ready for overnight delivery, worldwide



Specifications

Thermal 1

Thermal Wattage	Heatsink Θ _{s-a} ²	Heat Sink T _{Rise Above Ambient}
47 W	0.69 (°C/W)	32 (°C)
62 W	0.66 (°C/W)	41 (°C)
77 W	0.64 (°C/W)	49 (°C)


Mechanical

Material	6063-T5 Al Extrusion	
Finish	Black Anodized	
Weight	1.27 kg	
Regulatory	ory RoHS	

Size Diameter: 150 mm Height: 170 mm

The chart below summarizes the thermal performance of all round LED heatsink solutions with diameters 150 mm.

Heatsink Rise Above Ambient vs. Thermal Power Round Heatsinks Diameter 150 mm



LED Cooler R150-170 Heatsink


² Thermal resistance values are given as reference only and are measured in free air without airflow obstructions. Thermal resistance is measured from the bottom middle of the heat sink to ambient air, with a heat source of 19 cm². Actual thermal performance may vary by application and final product design should be tested to assure proper thermal performance.



www.nuventix.com

¹ All values are typical at 25°C unless otherwise stated.

Mechanical – LED Heatsink shown with Configurable heat sink



All dimensions are nominal and in mm unless otherwise stated. See product drawings for more detail.

Part Numbers

Part Number	Description	Notes
NX302100	Heatsink, R150-170, Vossloh Schwabe Luga Industrial, Panasonic, Citizen CLL050, Black	Contact sales for other heatsink options
NX302105	Heatsink, R150-170, Bridgelux RS, Bridgelux Vero 29, Black	Contact sales for other heatsink options

Nuventix reserves the right to make changes to the products or information contained herein without notice. No liability is assumed as a result of their use or applications. For additional information, please contact Nuventix directly.

