

- Cat.5e RJ45 PCB Jack Metal Shell: Copper Alloy, Nickel Plated

5. Recommaned Mounting Panel Nut torque is 20 to 25 lb-inch

- Cat.5e RJ45 PCB Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
- Cat.5e RJ45 PCB Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
3. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
4. IP67 rated when covered or fully mated with the appropriate mating connector

	AY NOT BE COPIED O MAY NOT BE PASSE VRITTEN PERMISSIO COPYRIGHT OF CON	TER CAD DRAW					2012 Draw. Appd. Norm	Nov. 19 Nov. 19	Name Vincent Ke J. Chaudry	Receptacle + Cover Assembly Kit with Cat. 5e RJ45 PCB Jack Version-II Nickel Plated Zinc Die-Cast Version
	WING MA AY, AND ITHOUT I	ĬĮ.					D-old			Drawing No.: 17K1A375
Directive 2002/95/EC RoHS Compliant	THIS DRA IN ANY W PARTY W OWNERS	DOT NO	a Rev.	original Changes	Date	Name	5			Part No.: SEE PART NUMBER TABLE  Sheet 1/1
<u>4</u> Д			3					2		1