

553-50042

Article Number: 553-50042

Description: Heat Shrink Label, 1.0" 1-Slit Single Sided, PO, Yellow, 500/BX



Base Data	
Local Order Number	553-50042
Type	HST24-8YE-S
Color	Yellow (YE)
Features and Benefits	<ul style="list-style-type: none"> • Slide Slit and optional center slits for easy wire insertion. • Smooth surface for clean and legible printing. • Supplied on a ladder style carrier so that markers can be kitted after printing. • A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
Quantity Per	box
Product Description	HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.
Short Description	Heat Shrink Label, 1.0" 1-Slit Single Sided, PO, Yellow, 500/BX
Product Dimensions	
Length L (Imperial)	0.95"
Length L (Metric)	24mm
Printable (Yes/No)	Yes
Variant	Thin-Wall
Width W (Imperial)	0.95"
Width W (Metric)	24mm
Height H (Imperial)	1.69"
Height H (Metric)	42.93mm
Diameter Min. (Imperial)	0.33"
Diameter Max. (Imperial)	1.0"
Outside Diameter Max. (Imperial)	1.0"
Outside Diameter Max. (Metric)	25.4mm
Wall Thickness WT (Imperial)	0.039"

553-50042



Product Dimensions	Wall Thickness WT (Metric)	0.99mm
	Flexibility	Flexible
	Print Method	Thermal transfer
	Recovered Diameter d (metric)	8.4mm
	Recovered Diameter d (imperial)	0.33"
	Supplied Diameter D (imperial)	1.024"
	Supplied Diameter D (metric)	26.0mm
	Thickness T (Metric)	3.0µm
	Width of Liner WL (imperial)	3.0"
	Width of Liner WL (metric)	76.2mm
	Width of Printable Area (imperial)	0.95"
	Width of printable area (metric)	24.10mm
	Material and Specifications	
Material		Polyolefin, cross-linked (PO-X)
Material Shortcut		PO-X
US MILSPEC		MIL-STD-202G Method 215K
Dielectric Strength (Metric)		19.7 kV min.
Flammability		UL 224 VW-1
Shrink Temperature		+194 °F (+90 °C)
Operating Temperature		-67°F to +275°F (-55°C to +135°C)
REACH Compliant (Article 33)		Yes
ROHS Compliant		Yes
Certification/Specification		UL224 125 °C 600V VW-1
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Markers per row	2
	Content Unit (BMEcat)	pack
	Weight (imperial)	1.48lbs
	Weight (Metric)	0.68kg