



SOLISTRAND* Pressure Type
Wire Connectors
 (Use Type "W" Tooling) **408- 2049**
 02 NOV 16 Rev M
 CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

WIRE SIZE (AWG) RANGE AND TYPE	424C LISTED	LR 7189 CERTIFIED
22- 16 Solid or Stranded	22- 16 AWG Solid or	22- 16 AWG Solid or Stranded
16- 14 Solid or Stranded	16- 14 AWG Solid or	16- 14 AWG Solid or Stranded
12- 10 Solid or Stranded	12- 10 AWG Stranded	12- 10 AWG Solid or Stranded
8- 600 MCM Solid or Stranded	8- 600 MCM AWG Stranded	8-4/0 AWG Solid or Stranded

NOTE: P/N's 324001 & 8-324001-0, UL Listed / CSA Certified, 22-20 AWG Solid or Stranded wire.
NOTE: Terminals and splices used with wire sizes 22- 16 AWG are stamped with 22- 18 in accordance with SAE- AS7928 (formerly MIL- T- 7928).
DANGER: To avoid equipment failure leading to serious injury or death, DO NOT use with aluminum wire.
DANGER: Pour éviter les bris d'équipement entraînant des blessures graves ou la mort, ne pas utiliser avec du fil d'aluminium.

©2015 TE Connectivity family of companies
 All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
 PRODUCT INFORMATION 1- 800- 522- 6752

For Regional Customer Service, visit our website at www.te.com

*Trademark. TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.



SOLISTRAND* Pressure Type
Wire Connectors
 (Use Type "W" Tooling) **408- 2049**
 02 NOV 16 Rev M
 CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

WIRE SIZE (AWG) RANGE AND TYPE	424C LISTED	LR 7189 CERTIFIED
22- 16 Solid or Stranded	22- 16 AWG Solid or Stranded	22- 16 AWG Solid or Stranded
16- 14 Solid or Stranded	16- 14 AWG Solid or Stranded	16- 14 AWG Solid or Stranded
12- 10 Solid or Stranded	12- 10 AWG Stranded	12- 10 AWG Solid or Stranded
8- 600 MCM Solid or Stranded	8- 600 MCM AWG Stranded	8-4/0 AWG Solid or Stranded

NOTE: P/N's 324001 & 8-324001-0, UL Listed / CSA Certified, 22-20 AWG Solid or Stranded wire.
NOTE: Terminals and splices used with wire sizes 22- 16 AWG are stamped with 22- 18 in accordance with SAE- AS7928 (formerly MIL- T- 7928).
DANGER: To avoid equipment failure leading to serious injury or death, DO NOT use with aluminum wire.
DANGER: Pour éviter les bris d'équipement entraînant des blessures graves ou la mort, ne pas utiliser avec du fil d'aluminium.

©2015 TE Connectivity family of companies
 All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
 PRODUCT INFORMATION 1- 800- 522- 6752

For Regional Customer Service, visit our website at www.te.com

*Trademark. TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.



SOLISTRAND* Pressure Type
Wire Connectors
 (Use Type "W" Tooling) **408- 2049**
 02 NOV 16 Rev M
 CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

WIRE SIZE (AWG) RANGE AND TYPE	424C LISTED	LR 7189 CERTIFIED
22- 16 Solid or Stranded	22- 16 AWG Solid or Stranded	22- 16 AWG Solid or Stranded
16- 14 Solid or Stranded	16- 14 AWG Solid or Stranded	16- 14 AWG Solid or Stranded
12- 10 Solid or Stranded	12- 10 AWG Stranded	12- 10 AWG Solid or Stranded
8- 600 MCM Solid or Stranded	8- 600 MCM AWG Stranded	8-4/0 AWG Solid or Stranded

NOTE: P/N's 324001 & 8-324001-0, UL Listed / CSA Certified, 22-20 AWG Solid or Stranded wire.
NOTE: Terminals and splices used with wire sizes 22- 16 AWG are stamped with 22- 18 in accordance with SAE- AS7928 (formerly MIL- T- 7928).
DANGER: To avoid equipment failure leading to serious injury or death, DO NOT use with aluminum wire.
DANGER: Pour éviter les bris d'équipement entraînant des blessures graves ou la mort, ne pas utiliser avec du fil d'aluminium.

©2015 TE Connectivity family of companies
 All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
 PRODUCT INFORMATION 1- 800- 522- 6752

For Regional Customer Service, visit our website at www.te.com

*Trademark. TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.



SOLISTRAND* Pressure Type
Wire Connectors
 (Use Type "W" Tooling) **408- 2049**
 02 NOV 16 Rev M
 CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

WIRE SIZE (AWG) RANGE AND TYPE	424C LISTED	LR 7189 CERTIFIED
22- 16 Solid or Stranded	22- 16 AWG Solid or Stranded	22- 16 AWG Solid or Stranded
16- 14 Solid or Stranded	16- 14 AWG Solid or Stranded	16- 14 AWG Solid or Stranded
12- 10 Solid or Stranded	12- 10 AWG Stranded	12- 10 AWG Solid or Stranded
8- 600 MCM Solid or Stranded	8- 600 MCM AWG Stranded	8-4/0 AWG Solid or Stranded

NOTE: P/N's 324001 & 8-324001-0, UL Listed / CSA Certified, 22-20 AWG Solid or Stranded wire.
NOTE: Terminals and splices used with wire sizes 22- 16 AWG are stamped with 22- 18 in accordance with SAE- AS7928 (formerly MIL- T- 7928).
DANGER: To avoid equipment failure leading to serious injury or death, DO NOT use with aluminum wire.
DANGER: Pour éviter les bris d'équipement entraînant des blessures graves ou la mort, ne pas utiliser avec du fil d'aluminium.

©2015 TE Connectivity family of companies
 All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
 PRODUCT INFORMATION 1- 800- 522- 6752

For Regional Customer Service, visit our website at www.te.com

*Trademark. TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.



SOLISTRAND* Pressure Type
Wire Connectors
 (Use Type "W" Tooling) **408- 2049**
 02 NOV 16 Rev M
 CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

WIRE SIZE (AWG) RANGE AND TYPE	424C LISTED	LR 7189 CERTIFIED
22- 16 Solid or Stranded	22- 16 AWG Solid or Stranded	22- 16 AWG Solid or Stranded
16- 14 Solid or Stranded	16- 14 AWG Solid or Stranded	16- 14 AWG Solid or Stranded
12- 10 Solid or Stranded	12- 10 AWG Stranded	12- 10 AWG Solid or Stranded
8- 600 MCM Solid or Stranded	8- 600 MCM AWG Stranded	8-4/0 AWG Solid or Stranded

NOTE: P/N's 324001 & 8-324001-0, UL Listed / CSA Certified, 22-20 AWG Solid or Stranded wire.
NOTE: Terminals and splices used with wire sizes 22- 16 AWG are stamped with 22- 18 in accordance with SAE- AS7928 (formerly MIL- T- 7928).
DANGER: To avoid equipment failure leading to serious injury or death, DO NOT use with aluminum wire.
DANGER: Pour éviter les bris d'équipement entraînant des blessures graves ou la mort, ne pas utiliser avec du fil d'aluminium.

©2015 TE Connectivity family of companies
 All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
 PRODUCT INFORMATION 1- 800- 522- 6752

For Regional Customer Service, visit our website at www.te.com

*Trademark. TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.



SOLISTRAND* Pressure Type
Wire Connectors
 (Use Type "W" Tooling) **408- 2049**
 02 NOV 16 Rev M
 CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

WIRE SIZE (AWG) RANGE AND TYPE	424C LISTED	LR 7189 CERTIFIED
22- 16 Solid or Stranded	22- 16 AWG Solid or Stranded	22- 16 AWG Solid or Stranded
16- 14 Solid or Stranded	16- 14 AWG Solid or Stranded	16- 14 AWG Solid or Stranded
12- 10 Solid or Stranded	12- 10 AWG Stranded	12- 10 AWG Solid or Stranded
8- 600 MCM Solid or Stranded	8- 600 MCM AWG Stranded	8-4/0 AWG Solid or Stranded

NOTE: P/N's 324001 & 8-324001-0, UL Listed / CSA Certified, 22-20 AWG Solid or Stranded wire.
NOTE: Terminals and splices used with wire sizes 22- 16 AWG are stamped with 22- 18 in accordance with SAE- AS7928 (formerly MIL- T- 7928).
DANGER: To avoid equipment failure leading to serious injury or death, DO NOT use with aluminum wire.
DANGER: Pour éviter les bris d'équipement entraînant des blessures graves ou la mort, ne pas utiliser avec du fil d'aluminium.

©2015 TE Connectivity family of companies
 All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
 PRODUCT INFORMATION 1- 800- 522- 6752

For Regional Customer Service, visit our website at www.te.com

*Trademark. TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.