

117-05302

HellermannTyton

Article Number: 117-05302

Description: Double-Head Cable Tie, 12" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg



Base Data	
Local Order Number	T50IDH9C2
Type	T50IDH
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • The tie contains a dual locking design to secure two bundles at once. • Head design can also provide spacing between parallel bundles. • Bent tail allows for quick insertion into head.
Quantity Per	bag
Product Description	The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Double-Head Cable Tie, 12" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225.0N
Length L (Imperial)	12.0"
Length L (Metric)	305.0mm
Bundle Diameter 2nd Loop Max. (Imperial)	1.5"
Fixation Method	None
Identification Plate Position	none
Number of Bundles	2
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19"
Width W (Metric)	4.7mm
Bundle Diameter Min. (Imperial)	0.06"

117-05302



Product Dimensions	Bundle Diameter Min. (Metric)	1.6mm
	Bundle Diameter Max. (Imperial)	1.5"
	Bundle Diameter Max. (Metric)	76.0mm
	Bundle Diameter 1st Loop Max. (Imperial)	3.0"
	Thickness T (Metric)	1.4mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	UL
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987