



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PS-615-HGULTRA

Power Strip - Agency-Approved Hospital/Medical Outlet Strip



Highlights

- Versatile power distribution strip
- 6 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- 15A resettable circuit breaker
- Double-fault safety protection

Description

Providing 15A capacity AC power distribution in a rugged all-metal outlet strip for 120V applications, Tripp Lite's PS-615-HGULTRA Power Strip is agency approved for use in physicians' offices, imaging centers, laboratories and medical facilities. Features include 6 hospital-grade receptacles with GFCI protection, 15-foot AC power cord and built-in resettable circuit breaker. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: Incorporates NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

Applications

- Reliable, agency-approved AC power distribution with hospital-grade receptacles and plug for use in physicians' offices, imaging centers, laboratories and medical facilities. Permits multiple items of electrical equipment to be utilized in rooms with limited duplex wall outlets.

Package Includes

- PS-615-HGULTRA Power Strip
- User manual with warranty information

Features

- Rugged all-metal housing withstands years of use without breakage
- 6 x NEMA 5-15R-HG hospital-grade output receptacles (2 with GFCI protection)
- 15-ft. AC cord with integrated, molded NEMA5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges.
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60Hz electrical compatibility
- Tested to UL (USA) and cUL (Canada)
- Agency approved for use in medical facilities

Specifications

OUTPUT	
Frequency compatibility	50 / 60 Hz
Circuit Breaker (amps)	15
Overload protection	15A circuit breaker
Outlet quantity / type	4 x NEMA 5-15R-HG; 2 x NEMA 5-15R-HG GFCI
Outlet orientation	Single row of 6
INPUT	
Recommended Electrical Service	15A 120V
Input connection type	NEMA 5-15P-HG
Input cord length (ft.)	15
Input cord length (m)	4.572
Voltage compatibility (VAC)	120
LEDS ALARMS & SWITCHES	
Switches	No power switch
PHYSICAL	
Shipping weight (lbs)	3.5
Shipping weight (kg)	1.6
Unit Dimensions (HWD/in)	1.5 x 13.75 x 2.5
Unit Dimensions (HWD/cm)	3.8 x 34.9 x 6.4
Shipping Dimensions (HWD/in)	2.25 x 15 x 6
Shipping Dimensions (HWD/cm)	5.7 x 38 x 15.2
Unit weight (lbs)	2.4
Unit weight (kg)	1.1
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole tabs and flanges enable mounting to a variety of surfaces. Keyhole spacing 10.75" (26cm) center to center; 1.75" (4.4cm) center to edge of strip
Receptacle Color	White
AC line cord color	White
CERTIFICATIONS	
UL1363 (Power Tap)	TUV tested to UL1363
cUL / CSA (Canada)	TUV tested to CAN/CSA C22.2 No. 21-95
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=2923.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.