



1. INSERT A 1.57[.062] THICK DUMMY PC BOARD INTO CARD SLOT DURING SOLDERING PROCESS.
2. DATUMS AND DIMENSIONS ARE ESTABLISHED BY CUSTOMER.
3. PART NUMBER AND DATE CODE(OPTIONAL), LOCATED APPROXIMATELY AS SHOWN.
4. .400 DIMENSION REFERENCES CARD SLOT DEPTH.
5. HOUSING—GLASS FILLED POLYESTER, WHITE. CONTACTS—ALLOY CDA-195.
6. CONTACTS—3.81 $\mu$ m[.000150] MIN TIN—LEAD OVER 0.76 $\mu$ m[.000030] MIN NICKEL.
7. PIN LENGTH RECOMMENDED FOR USE WITH 3.18 $\pm$ 0.51[.125 $\pm$ .020] THICK PRINTED CIRCUIT BOARD.
8. CONTACTS—3.81 $\mu$ m[.000150] MIN MATTE TIN OVER 0.76 $\mu$ m[.000030] MIN NICKEL.

5-145339-1  
 145339-1  
 PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN M. MORRIS 25SEPT98	Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS: mm [INCHES]		CHK C. REIFSNYDER 25SEPT98	NAME CONNECTOR ASSY, 5 POSITION, SELECTIVELY LOADED, HIGH CURRENT	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD C. REIFSNYDER 25SEPT98	PRODUCT SPEC 108-9045	
0 PLC ± -		APPLICATION SPEC 114-9005		
1 PLC ± -		SIZE A1	CAGE CODE 00779	DRAWING NO. 145339
2 PLC ± 0.13[.005]		WEIGHT -	RESTRICTED TO -	
3 PLC ± -		CUSTOMER DRAWING		
4 PLC ± -		SCALE 4:1	SHEET 1 of 1	REV B
ANGLES ± -				
MATERIAL 5				
FINISH 6				