



OM7802

Low-noise amplifier evaluation board using BGU7003 matched for CMMB

Demo board description

The BGU7003 LNA evaluation board simplifies the evaluation of the BGU7003 LNA for the Chinese Mobile Multimedia Broadcast at frequencies ranging from 400 MHz to 800 MHz. The evaluation board enables testing of the device performance and requires no additional support circuitry. The board is fully assembled with the BGU7003, including the input and output matching circuitry as well as a decoupling capacitors to optimize the performance. The board is supplied with two SMA connectors for input and output connection to RF test equipment. The BGU7003 board is optimized for 2.5 V operation and consumes about 5 mA.

Features

- Two SMA connectors for input and output connection to RF test equipment
- Evaluation of the power on settling time t_{on} and the power off settling time t_{off}

Descriptive summary

Evaluation board content

BGU7003 LNA evaluation board in ESD safe packing

Applications

Applications for CMMB ranging from 400 MHz to 800 MHz.

All information on this product information page is subject to the subsequent disclaimers:

- General product disclaimer
- Quality and reliability disclaimer

Documentation for this product

[Download all documentation \(zip\)](#)

Filename	Type	Format	Title	Date
AN11097	Application note	pdf	CMMB LNA with BGU7003, 400 MHz to 800 MHz (v.1.0)	2012-03-29

Demo boards

Type number	Ordering code(12NC)	Orderable part number	Products status	Region	Distributor	In stock	Order quantity	Inventory date	Buy online
OM7802/BGU7003/CMMB	9340 660 72598		Volume production						

Products

Type number	Description	Status	Quick access
BGU7003	Wideband silicon germanium low noise amplifier MMIC		Download datasheet Order sample

Support

If you have any questions related to this product please contact our support team via the support form:

<http://www.nxp.com/techsupport/>