

Pressure compensation element - A-EXB-20-66L-N-S - 1411117

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Pressure compensation element, Nickel-plated brass, Application: Ex, Connecting thread: M20, Color: silver

Why buy this product

- reduces the formation of condensation



Key Commercial Data

Packing unit	5 STK
GTIN	 4 046356 922326
GTIN	4046356922326

Technical data

Dimensions

Length	32 mm
Length without connecting thread	17 mm
Connecting thread diameter	20 mm
Wrench size, union nut	30 mm
Hexagon angular dimension	33 mm
Length of the connecting thread	15 mm

Ambient conditions

Degree of protection	IP66
Ambient temperature (operation)	-60 °C ... 130 °C

General

Material	Nickel-plated brass
O-ring material	Silicon
Thread type on connection side	M20
Torque	7 Nm (Installation torque)

Pressure compensation element - A-EXB-20-66L-N-S - 1411117

Technical data

General


Water flow rate	1,89 cm ³ / min (at 0 bar)
Air flow rate	48 l/min (at 1 bar)
Color	silver
Assembly instructions	Mount at the lowest point of the housing, including ribbed counter nut (ensure correct orientation when mounting, the grooved side must be pointing towards the wall)
Standards/specifications	IEC 60079-0, -1, -7, -31
	EN 60079-0, -1, -7, -31
Manufacturer	CMP
Manufacturer Designation	781EM2
Suited for EX-applications	yes

Standards and Regulations

Standards/regulations	IEC 60079-0, -1, -7, -31
	EN 60079-0, -1, -7, -31
ATEX	Sira 10ATEX1307U
	781D: Ex II 2 GD Exd IIC Gb, Ex ta IIIC Da, 781E: Ex II 2 GD Exe IIC Gb, Ex ta IIIC Da
IECEX	IECEX SIR 10.0149U
	781D: Ex d IIC Gb, Ex ta IIIC Da 781E: Ex e IIC Gb, Ex ta IIIC Da

Drawings

Dimensional drawing



Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>