

**The IE-Power/5V Power Supply is a Compact, Extended Temperature (IE) AC to DC Power Source.**

### Features and Benefits

- Universal AC Input/Full Range
- Short circuit/Overload/Over voltage protection
- Low no load power consumption <0.75W
- Compact, fully isolated enclosure
- Includes 12" Barrel-Connector Power Cable
- Built-in DIN Rail mount
- DC OK active LED signal
- Comprehensive 3-year warranty



### Technical Specifications

#### Regulatory Approvals:

- FCC Class B
- UL 508 / cUL, CE
- TUV EN 60950-1
- NEC Class 2 / LPS Compliant

#### Dimensions

3.54"H x 0.89"W x 3.94"D  
(9 x 2.25 x 10 cm)

#### Shipping Weight

0.42 lbs (0.19 kg)

#### Power Information

Range: 85 ~ 264 VAC, 120 ~ 370 VDC  
Input: 47 ~ 63Hz, 0.33A/115 VAC  
0.21A @ 230 VAC  
Output: 5V @ 2.0A

#### Operating Temperature

-4° to +158° F  
(-20° to +70° C)  
20 to 90% (non-condensing)

#### Storage Temperature

-40° to +185° F  
(-40° to +85° C)  
10 to 95% (non-condensing)

#### MTBF


584K hours (min.)

The IE-Power/5V Power Supply adapter is a single output, AC to DC power adapter. It features extended operating temperatures (-20° to +70° C) which make it just right for use with products such as the IE-MiniMc Series and IE-MiniFiberLinX-II, to name a few.

The compact size of IMC Networks' IE-Power/5V makes it ideal for space restricted, DIN Rail applications in industrial, automation and military environments including control cabinets and computer rooms. The beneficial low no load power consumption feature expands the use of this power supply to smaller IT applications as well. Additionally, the fully isolated, plastic enclosure protects operators from electrical shock.

Free-air convection cooling eliminates the need for noisy, failure-prone fans. Short circuit, overload and over voltage protection protect your hardware from transient voltage spikes. The IE-Power/5V comes standard with a comprehensive 3-year warranty.

IMC Networks products that support the IE-Power/5V include: IE-MultiWay, MiniMc, IE-MiniMc, Giga-MiniMc, IE-GigaMiniMc, MiniMc-Gigabit, IE-MiniFiberLinX-II, AccessConverter and the IE-ModeConverter.



The IE-Power/5V mounted to a DIN Rail and connected to an IE-Giga-MiniMc.

PART NUMBER	DESCRIPTION
IE-Power/5V	
806-39753	IE-Power/5V Module, AC to DC DIN Rail Power Adapter (-20° to +70° C)

#### IMC Networks

##### Headquarters

19772 Pauling  
Foothill Ranch, CA 92610  
TEL: 949-465-3000  
FAX: 949-465-3020  
sales@imcnetworks.com

#### IMC Networks

##### Europe

Herseltsesteenweg 268  
B-3200 Aarschot, Belgium  
TEL: +32-16-550880  
FAX: +32-16-550888  
eurosales@imcnetworks.com

#### IMC Networks

##### Eastern US/Latin America

28050 U.S. Hwy. 19 North, Suite 306  
Clearwater, FL 33761  
TEL: 727-797-0300  
FAX: 727-797-0331  
latinsales@imcnetworks.com

#### IMC Networks

##### Fiber Consulting Services

For information call:  
TEL: 949-465-3000  
1-800-624-1070 (US/CAN)  
+32-16-550880 (Europe)  
fcs@imcnetworks.com