C51

AT83C25OK with OMNIKEY Firmware

PRE-CERTIFIED SMART CARD READER SOLUTION FOR **PCMCIA LINK**

AT83C25OK is based on an Atmel C51 MCU and includes OMNIKEY® firmware. It is a single-chip ready-to-use solution that can be quickly and easily integrated into any PCMCIA smart card reader.



Key Features & Benefits

- Single-chip Solution
- Quick Time-to-Market
- Fast and Easy EMVCo Certification
- Supports all Smart Cards
- PCMCIA (PC-Card) Connection

Compliance with:







Applications

- PCMCIA Smart Card Reader
- Notebook
- Set Top Box
- Personal Digital Assistant (PDA)





AT83C25OK PCMCIA SMART CARD READER SOLUTION

Atmel Corporation

2325 Orchard Parkway San Jose, CA 95131

USA

TEL.: (1)(408) 441-0311 FAX.: (1)(408) 487-2600

Regional HeadquartersEurope

Atmel Sarl Route des Arsenaux 41 Case Postale 80 CH-1705 Fribourg Switzerland

TEL.: (41) 26-426-5555 FAX.: (41) 26-426-5500

Asia

Room 1219 Chinachem Golden Plaza 77 Mody Road Tsimshatsui East Kowloon Hong Kong

TEL.: (852) 2721-9778 FAX.: (852) 2722-1369

Japan

9F, Tonetsu Shinkawa Bldg. 1-24-8 Shinkawa Chuo-ku, Tokyo 104-0033 Japan

TEL.: (81) 3-3523-3551 FAX.: (81) 3-3523-7581

Products Contact

La Chantrerie BP 70602 44306 Nantes Cedex 3 France

TEL.: (33) 2 40 18 18 18 FAX.: (33) 2 40 18 19 60

e-mail

literature@atmel.com

Web Site

http://www.atmel.com

© Atmel Corporation 2003. All rights reserved. Atmel*, and combinations thereof are the registered trademarks of Atmel Corporation or its subsidiaries.

OMNIKEY* is a registered trademark of OMNIKEY AG, Linux* is a registered trademark of Linux Torvalds, Windows* is a registered trademark of Microsoft Corporation. Other terms and product names may be the trademarks of others.

4030A-8051-05/03/10M

AT83C25OK is a highly integrated solution, including OMNIKEY firmware and associated drivers, for any smart card reader using a PCMCIA link.

It allows customers to reduce time-to-market as it is compliant with ISO 7816, EMV 2000 and WHQL certified.

The AT83C25OK combines Atmel and OMNIKEY's expertise in smart card reader development and in-system integration.

To implement this turnkey solution, customers only have to include the appropriate drivers in their host software (Windows® 98/ME/NT4/2000/XP, CE.NET, Linux®).



Product Features

- Host Interface
 - PCMCIA (PC-card)
 - PC/SC Compliant
- Supported Smart Cards
 - Asynchronous & Synchronous
- Smart Card Power Supply
 - 1.8V (20 mA), 3 or 5V (60 mA)
 - Short Circuit Current Limitation
 - Power Up/Power Down Management

- Smart Card Management
 - Presence and Insertion/Extraction
 Detection
- 4 kV ESD Protection on Card Pins
- AT83C25OK Power Supply
 - 3.6 to 5.5 Volts
 - 100 µA Standby Mode
- Temperature Range
 - **-**40 to +85°C

AT83C25OK Reference Design (AT89RFD-06)



Technical Package Available on CD-ROM

- Specifications
 - Schematics & Bill of Material
 - Software Drivers
 - Test Utilities



AT83C25OK Reference Design

Contact Information

Technical Support: mcu@atmel.com

Ordering Information

Part Numbers	Description
Development Tool	
AT89RFD-06	Reference Design with three samples
Devices	
AT83C25OK100-RDTIL	VQFP64 in Tray
AT83C25OK100-RDRIL	VQFP64 in Reel