



Article Number: 151-00455

Isolator Mount for separating .25" tubing, Max Bundle Diameter .25", TPV, Black, 500/pkg Description:

Base Data		
	Land Order Niverban	ICO AVOTOLIA
	Local Order Number	ISO4X250H1
	Туре	ISO4X250
	Color	Black (BK)
	Features and benefits	<ul> <li>Design provides quick and easy assembly.</li> <li>Isolator mount dampens harmful vibrations on bundles</li> <li>Material is durable, chemical and abrasion resistant, and remains flexible in low temperatures.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton's isolator mount is used to align and separate 1/4" tubing or brake lines. Easy to assemble, the isolator dampens vibrations and can be used with up to four brake lines. Mounting the isolator can be accomplished with HellermannTyton's standard cable ties, button head ties and any of HellermannTyton's heavy equipment mounts. Mounting is optional, but recommended for long runs. The isolator is durable, chemical and abrasion resistant, and remains flexible in low temperatures.
	Short Description	Isolator Mount for separating .25" tubing, Max Bundle Diameter .25", TPV, Black, 500/pkg
Product Dimensions		
	Width W (Imperial)	0.9"
	Width W (Metric)	23.4mm
	Bundle Diameter Max. (Imperial)	0.25"
	Bundle Diameter Max. (Metric)	6.4mm
Material and Specifications		
	Material	Thermoplastic vulcanized (TPV) rubber
	Material Shortcut	TPV
	Flammability	UL 94 HB
	Operating Temperature	-110°F to +347°F (-79°C to +175°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes

generated on: 4/29/2017

## 151-00455



Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces

generated on: 4/29/2017