

NOTES:

1. SPECIFICATIONS:

ELECTRICAL:
 WITHSTANDING VOLTAGE: MINIMUM 1000 V RMS @ SEA LEVEL
 INSULATION RESISTANCE: INITIAL 5000 MEGOHMS MAXIMUM,
 1000 MEGOHMS MIN. AFTER ENVIRONMENTAL TESTING.
 CONTACT RATING: 5 AMPS
 CONTACT RESISTANCE: 2.7 MILLIOHMS MAX.

MATERIALS:
 INSULATOR: BLACK UL94V-0 RATED GLASS FILLED NYLON
 CONTACT(O30-1953-000): COPPER ALLOY
 CONTACT AREA PLATING: GOLD OVER NICKEL,
 CONNECTOR SHELL: STEEL, PLATING ZINC WITH CLEAR CHROMATE.


ENVIRONMENTAL:
 OPERATING TEMPERATURE: -65°C TO +125°C

TERMINATION:
 CRIMP WILL ACCOMMODATE # 20 TO 28 AWG WIRE.
 TERMINATION-TOOLS:
 CRIMP TOOL: M22520/2-01
 INSERTION/EXTRACTION TOOL: CIET-20-HDB
 POSITIONER: EP-580


2. DIMENSIONS IN [] ARE IN MILLIMETERS.

DRAWING REVISIONS			
REV	DOCUMENT	APP	DATE
A	DO 05-1094	AKB	1/7/06
B	ECN 06E208		

NUMBER OF POSITIONS	SELECTIVE GOLD FLASH PLATING (.120" [3.05] MTG. HOLES)		CONTACTS	DIMENSION							FRONT MOUNTING HOLE DIMENSIONS		REAR MOUNTING HOLE DIMENSIONS																																					
	PART NO.	FACTORY NO.		"A"	"B"	"C"	"D"	"E"	"F"	"G"	"X"	"Y"	"X"	"Y"																																				
9	DEUH-9S	702 13 09 001	INCLUDED	1.213	.984	.640	.308 [7.82]	.494 [12.55]	.759 [19.28]	.422 [10.72]	.874 [22.20]	.513 [13.03]	.806 [20.47]	.449 [11.40]																																				
	DEUH-9S-FO	702 13 09 005	NOT INCLUDED	[30.81]	[24.99]	[16.26]									[19.28]	[22.20]	[20.47]																																	
15	DAUH-15S	702 13 15 001	INCLUDED	1.541	1.312	.968									.308 [7.82]	.494 [12.55]	1.083 [27.51]	.422 [10.72]	1.202 [30.53]	.513 [13.03]	1.134 [28.80]	.449 [11.40]																												
	DAUH-15S-FO	702 13 15 005	NOT INCLUDED	[39.14]	[33.32]	[24.59]																	[27.51]	[30.53]	[28.80]																									
25	DBUH-25S	702 13 25 001	INCLUDED	2.088	1.852	1.508																	.308 [7.82]	.494 [12.55]	1.625 [41.28]	.422 [10.72]	1.743 [44.27]	.513 [13.03]	1.674 [42.52]	.449 [11.40]																				
	DBUH-25S-FO	702 13 25 005	NOT INCLUDED	[53.04]	[47.04]	[38.30]																									[41.28]	[44.27]	[42.52]																	
37	DCUH-37S	702 13 37 001	INCLUDED	2.729	2.500	2.156																									.308 [7.82]	.494 [12.55]	2.272 [57.71]	.422 [10.72]	2.391 [60.73]	.513 [13.03]	2.326 [59.08]	.449 [11.40]												
	DCUH-37S-FO	702 13 37 005	NOT INCLUDED	[69.32]	[64.50]	[54.76]																																	[57.71]	[60.73]	[59.08]									
50	DDUH-50S	702 13 50 001	INCLUDED	2.635	2.406	2.062																																	.308 [7.82]	.494 [12.55]	.534 [13.56]	.422 [10.72]	2.297 [58.34]	.623 [15.82]	2.218 [56.34]	.555 [14.10]				
	DDUH-50S-FO	702 13 50 005	NOT INCLUDED	[66.93]	[61.11]	[52.37]																																									[13.56]	[58.34]	[15.82]	[56.34]



ROHS COMPLIANT



UNITS	ENGLISH	PRO/E	Cinch	
DO NOT SCALE DRAWING	DRAWN BY V. SKUZA	DATE 06/24/05	TITLE D*U SERIES CRIMP & POKE CONNECTOR SKT. ASS'Y (.120" MTG HOLES)	
	DESIGN ENGINEER A. BALI	06/24/05	MATERIAL CONTROL SPEC NUMBER	
	DESIGN ENGINEERING MGR. A. SHAH	07/09/05	MATERIAL SPEC NUMBER	FINISH PROJECT NUMBER C14740
	MFG. ENGINEERING J. OCEGUERA	07/07/05	CAD FILE NUMBER DXUH-XXS	DRAWING NUMBER D*UH-XXS
	QUALITY ASSURANCE A. VAZQUEZ	07/06/05	CAGE IDENT NO. SIZE 71785 B	SCALE 1:1 SHEET 1 OF 1

MODELED BY:
V. SKUZA
1700 FINLEY RD
LOMBARD, IL. 60148