

111-02901



Article Number: 111-02901

Description: Standard Cable Tie, 14" Long, 30lb Tensile Strength, PA66, Black, 100/pkg

Base Data	
Local Order Number	T30XL0C2
Type	T30XL
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Standard Cable Tie, 14" Long, 30lb Tensile Strength, PA66, Black, 100/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	30.0lbs
Minimum Tensile Strength (Metric)	135.0N
Length L (Imperial)	14.0"
Length L (Metric)	365.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14"
Width W (Metric)	3.5mm
Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.5mm
Bundle Diameter Max. (Imperial)	4.13"

111-02901



Product Dimensions	Bundle Diameter Max. (Metric)	105mm
Material and Specifications	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
	Logistic and Packaging	Package Quantity (Imperial)
Package Quantity (Metric)		100
Customs Number(Schedule B)		3926909987
Content Unit (BMEcat)		bag